

1D Laser Barcode Scanner



TBS-6606

Features:

- Auto Data Detection.
- High-performing laser scan engine.
- Ergonomic design for maximum user comfort.
- Support all common 1D barcodes and popular interface.



1D Code



Laser Aimer



Cable 1.5m



Restaurant



Drop test 1.5M



USB



RS232



Retail

Performance Parameters

Light Source	650nm laser (Safe visible laser diode)
Decode Capability	UPC-A, UPC-E, EAN-8, EAN-13, ISSN, CODE39, CODE 39 Full ASCII, MSI, CODE93, Plessey, CODE128, Codebar, Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, Standard 2 of 5, ISBN, Code 11, Code 32(Italian pharm code), Code 39 extended, GS1-128 and ITF-14, SISAS, GS10 mnidirecional, RSS14, GS1 Limited, Aviation25, China Post.
Scan Type	Single Laser
Scan Speed	≥150 times/s
Scan Mode	ManuallyContinuous/Automatic inductive Scanning (Optional)
Scan Angle	Skew 55°,Rotation 30°,Pitch 65°
Resolution	≥3mil
Depth of field	10-280mm(0.33mm, PCS90%)
Bit Error Rate	Less than 1/5million
Interface	USB-HID, USB-COM, PS2, RS232

Physical Parameters

Dimension	83mm*70mm*172mm
Weight	126.6g
Material	ABS+PC
Cable	1.5M straight

Environmental Parameters

Operating Temperature	-20°C~50°C
Storage Temperature	-40°C~70°C
Relative Humidity	5%~95%(Non-condensing)
Drop Resistance	Withstands multiple times 1.5 meters drops to concrete

Electrical Parameters

Voltage	DC5V±1%
Working Current	85mA